

# 9460 AREA LIGHT



A portable floodlight, housed inside a Peli case with cool operating temperatures and silent operation.

The 9460 features Intelligent Output Control and is able to display current battery life and calculate remaining run time. It allows the user to regulate the light intensity,

so next time a job overruns you can extend the battery life and see, to the minute, how long you have left. It has a retractable handle and stainless steel ball bearing wheels & can be programmed via a Peli app.



## SPECIFICATIONS

Lumens:	Up to 12000
Lamp Heads:	2
Head Rotation:	360°
Number of LEDs:	20
Light Mode:	Floodlight
Beam Spread:	120°
LED Life (hrs):	50000
IP Rating:	54

## SIZE & WEIGHT

Dimensions:	591 x 356 x 235 mm
Maximum Height:	2010 mm
Weight:	27.70 kg

## COLOURS



## BATTERY

Battery:	12V Rechargeable, Sealed Lead Acid (SLA) (included)
Run Time:	Low - 24h High - 3h
Recharge Time:	8h (from full discharge)

### ALSO AVAILABLE THE 9460M

With a multi-terrain trolley and XL wheels it provides easy transport over rough terrain. Please enquire for full details.



**CAUTION:** The 9460 contains sealed lead acid batteries that can generate hydrogen gas when charging. It is imperative that these products are charged, as instructed, with the case lid open to allow any gases to escape as charging with the lid closed poses a significant hazard. Failure to abide by this instruction could result in injury and/or damage to property. Please refer to the warnings provided in the instructions for the unit and on a decal affixed to the inside of the case adjacent to the cavity where the charger unit is packed.